



SPIDOO SUBINOX 7
Code : 002307
Gencod : 3325310023073

STAINLESS STEEL BODY

Starting panel
not required



Adjustable
height for
well & tank
installation

CHARACTERISTICS

- ✓ Power: 1100 watts
- ✓ Max. flow: 5,5 m³ / hour
- ✓ Max. pressure: 5,6 bar
- ✓ Max. height: 56 m
- ✓ Max. submersion depth: 20m
- ✓ Weight: 10 kg
- ✓ Stainless steel body
- ✓ Electric wire (extendable): 20 m
- ✓ Number of propellers: 7
- ✓ Pump diameter: 98 mm
- ✓ Outlet: F 33/42
- ✓ Supplied with: polypropylene nipple M33/42-M26/34 + adjustable height 11cm

KEY POINTS

Borehole pump

Power ñ Silence ñ Reliability : stainless steel body, cover & strainer.

Ready to be used

No setting. Simple use. Starting panel not required.

PACKAGING

Quantity per pallet = 60 pieces

ACCESSORIES

DIPRA

107 rue du Ruisseau
 38297 SAINT QUENTIN FALLAVIER
 Tél. : (33) 04.74.95.56.65
 Fax : (33) 04.74.94.36.94

GARDEN
Pump
Borehole pump